

PRODUCT INFORMATION SHEET

600-ml lubricator



Product description

Manual lubricator for workshop applications. Designed for use in heavy industry, industrial machines, construction machines, cars, delivery trucks, and lorries.

Characteristics

- 4-jaw tip;
- maximum working pressure: 700 bar;
- M10 x 1 connection threads;
- 300-mm hose with a 4-jaw tip and a 150 mm steel tip included;
- double piston with additional sealing;
- 2 vent valves;
- zinc-cast head;
- plunger for the pump features high accuracy of fitting to the shape of the cylinder (no apparent lubrication);
- lacquered enclosure with a non-slip rubber guard;
- pumping volume: 2.4 cm³;

Technical data

HT8G908	5902801000997	600 cm ³	1 pc.	10 pcs.



Distributor:

RU 000 «ГТВ РУС»
140073 Московская область
Люберецкий район, пос.Томилино
мкрн. Птицефабрика, Литер 7А

CZ GTV Czech Distribution s.r.o.
CTPark Ostrava, Na Rovince 879
720 00 Ostrava Hrabová

HR GTV Croatia d.o.o.
Kovinska 4a, 10000 Zagreb, Hrvatska

Högert Technik GmbH
Pariser Platz 6a
10117 Berlin, Deutschland
Importer: GTV, Przejazdowa 21
05-800 Pruszków, Polska